

TAHOE CHIMNEY & FIREPLACE

Guidelines and Procedures

In the Morning:

Arrive at least 30 min (or more) at the garage before the first job to make it there on time.

If you are running late for any reason - contact the first customer of the day to confirm if they are ok with your lateness. In SF Change job status to **Delayed**. Text the manager "121" (121 code means: I will be starting the day late, the customers knows and is ok with that, code 120 means: I called and texted the client, but they did not answer yet)

CLOCK - IN on app and check for deliveries around the house/garage

Get Van ready with:

- Runners
- Garbage bags
- Tool Batteries
- Charged Flashlight
- Paper Towels
- Windex
- Fatwood bundles
- Check the Route and **Job Notes** in Service Fusion App
- Load Parts needed
- Charge your Phone!
- Check Fuel

Check oil and Coolant Once a week

At the End of the Day:

Charge tool batteries

- Clean van (remove trash and restock leftover chimney parts from the day into the garage)
- Organize deliveries in the garage
- Clean driveway of boxes, crates, trash etc.
- Upload any remaining photos or notes.
- CLOCK OUT on app

GENERAL Home Service Procedure:

Size up as you drive up (assess chimney type, diameter and roof access from outside)

Change Job Status to **ON SITE** in app

Check Client's First name

Clean Face, Clean Hand

Grab a Runner (or other tools) and Greet with a SMILE

"Good Morning "Steve" my name is I am here to take care of your fireplace.

" How are you today?"

BEFORE YOU ENTER: " Are my shoes OK in your home?" (with white carpets wear plastic booties anyway)

Setup inside (Place all tools on Runner or hearth extension, **Never** on Carpet.

ASK "How has it been working for you?" make notes of potential problems. Just say: "We will look into that" (don't explain problems at this point until you look at the system, share your knowledge after the service - it saves time

Explain: "The service should take 30-60 min and we will just be making noise with our vacuum. I will let you know at the end if we find any issues you should know about."

Do Great Work! (SEE PROCEDURES ON PAGES BELOW)

- keep your work area and yourself tidy as much as you can,
- minimize ash on floor or runner,
- vacuum your clothing if needed not to spread the dust around the house as you walk
- Keep runner spread nicely flat
- <u>Do Not</u> lay viper or brushes <u>on the Runner</u> (put it on hearth or next to stove so it does not get stepped on or leaves soot onto the runner - soot gets easily tracked from Runner onto Carpet.
- Make the area around appliance **cleaner than** before you arrived.

1st Clean the **Chimney**

2nd Clean the **Firebox** (cleaning the firebox before the chimney is a waste of time)

3rd Clean the Glass

4th Clean the **Area** around the Fireplace CLEAN CLEAN!

Give **Oral report**, explain problems if needed.

Leave FATWOOD and WOODBURNING HANDBOOK after sweeps. (if applicable)

Ask "Would you be able to write us a check today?" Make Payable to Tahoe Chimney & Fireplace.


Ask "Would you like us to call you next year?" If YES, write REGULAR in <u>App Notes.</u>
Leave a **Business Card** and say "Give us a call anytime with any questions!" "Thank You, Have a Nice Day! Remember to SMILE.

Update info on Service Fusion App: Make **Notes**.Fill out **Custom Fields**, Upload **photos** of **Appliance**, **Chimney and anything relevant**.

LADDER SAFETY

Procedures

1. Use **1x4 Rule** for ladder angle



2. **Attach** the ladder to the roof for safety







3. Use ladder hooks + Three 1.5"long screws for ladders laid on the roof (one person on ladder at a time). When you remove hooks later - leave screws in the roof.

4. Dig a grove in the ground for ladder footing




- 5. Dig an extra 5" deep groove on sloped surfaces
- 6. Screw ladder feet to deck in slippery conditions (with roofing screws)

- 7. Always **face the ladder** when walking down on roof (or you'll fall forward and tumble)
- 8. Be Extra careful when working with SILICONE! It will make roof and ladder extremely slippery.
- 9. DO NOT put screws into a "screwless" roof, before you consult with the Client. Let them know: "As a precaution we always screw a ladder hook onto the roof. The screws we use are professional roofing fasteners and they do not leak after we leave them in your roof. I understand if you still prefer no screws used, but it may make chimney access much harder/impossible"









TOOL SAFETY



Wear gloves AT ALL TIMES!



Stitches are expensive, painful and no work for a week or longer









Wear Goggles!



When using Sawzall, Skilsaw, Grinder or Drilling into metal







